

## Linear Actuator

- 12, 24 or 48V power supply.
- Integrated brake for self locking.
- Overload protection via internal slip clutch.
- Emergency manual override via hex drive in end of actuator.
- Built in controller, simply send distance and speed command via CAN.
- Various strokes and power ratings available.
- IP66 rated.



Order number	Push max. (N)	Pull max. (N)	*Self-lock min. (N) Push	*Self-lock min. (N) Pull	Pitch (mm/spindle rev.)	*Typical speed (mm/s) Load		Standard stroke lengths (mm) In steps of 50 mm	*Typical amp. (A) 12 V	
						No	Full		No load	Full load
Linear A	6800	6800	13000	13000	8	11	7	100 - 999**	4.5	17
Linear B	2600	2600	3400	3400	12	40.7	30.6	100 - 999	4.5	21
Linear C	4500	4500	5800	5800	12	23.1	17.8	100 - 999**	4.5	20.7
Linear D	6800	6800	8800	8800	12	15.5	11.9	100 - 999**	4.5	21
Linear E	2000	2000	2600	2600	16	54.3	43	100-999	4.5	21.5
Linear F	3400	3400	4400	4400	16	30.8	25	100-999**	4.5	21.4
Linear G	5600	5600	6600	6600	16	20.7	17	100-999**	4.5	21.5
Linear H	1700	1700	2200	2200	20	68	52	100 - 999	4.5	22
Linear J	500***	500***	1000	1000	20	160	135	100 - 999	4.5	20

Contact us for more details:

UK Office: [sales@dcemotorsport.com](mailto:sales@dcemotorsport.com)  
US Office: [salesusa@dcemotorsport.com](mailto:salesusa@dcemotorsport.com)

[www.dcemotorsport.com](http://www.dcemotorsport.com)