

SINGLE-FREQUENCY, MULTI-GNSS ANTENNA



The A25 GNSS antenna is designed to support millimeter-level accuracy on land and marine applications. The A25 GNSS antenna offers support for present and future GNSS signals, including GPS, GLONASS, BeiDou, and Galileo. A25 is a multi-GNSS precision antenna and is ideal for various applications including surveys, single-frequency RTK positioning and navigation, precise guidance, and machine control. Use the A25 antenna in challenging environments (such as near buildings and foliage) for superior multipath mitigation, stable phase center and strong SNR's, even at low elevations. The A25's ruggedized housing is made of an aluminum base that has been pretreated for the marine environment and will withstand salt, fog, and spray. The antenna easily passes the two-meter pole drop test.

GNSS Sensor

Signals Received: GPS L1, GLONASS G1, BeiDou B1, Galileo E1, SBAS, and L-band

GNSS Frequency: 1.525 to 1.615 GHz

LNA Gain: 30 dBn

LNA Noise: 2.0 dB, typical

L-Band Sensor

L-Band

Frequency: 1.525 - 1.585 GHz

L-Band LNA Gain: 30 dB

Power

Input Voltage: 3.3 to 12 VDC
Input Current: 12 mA, typical

Mechanical

Enclosure: Aluminum base with Lexan™ plastic cap
Dimensions: 4.7 H x 15.2 D (cm)

1.8 H x 6.0 D (in)

Weight: .40 kg (.88 lbs)

Mount: 5/8 inch female thread

RF Connector: TNC (straight)

Environmental

Storage

Temperature: -40° C to +85° C (-40°F to +185°F)

Operating

Temperature: -40° C to +70° C (-40°F to +158°F)

Enclosure Rating: IP69K

Shock/Vibration: EP455

Phase Center

Variation: Less than 2 mm at GPS L1, for elevations above 15 degrees

Hemisphere GNSS

8515 E. Anderson Drive
Scottsdale, AZ 85255, USA

Phone: +1 (480) 348-6380

Toll-Free: +1 (855) 203-1770

Fax: +1 (480) 270-5070

precision@hgns.com
www.hgns.com